



US009636926B2

(12) **United States Patent**
Aoyagi

(10) **Patent No.:** **US 9,636,926 B2**

(45) **Date of Patent:** **May 2, 2017**

(54) **PRINT MEDIUM, PRINT MEDIUM UNIT
AND PRINTING DEVICE**

(71) Applicant: **Seiko Epson Corporation**, Tokyo (JP)

(72) Inventor: **Naohiko Aoyagi**, Azumino (JP)

(73) Assignee: **Seiko Epson Corporation**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/909,107**

(22) PCT Filed: **Jul. 28, 2015**

(86) PCT No.: **PCT/JP2015/003767**

§ 371 (c)(1),

(2) Date: **Jan. 30, 2016**

(87) PCT Pub. No.: **WO2016/017145**

PCT Pub. Date: **Feb. 4, 2016**

(65) **Prior Publication Data**

US 2016/0257130 A1 Sep. 8, 2016

(30) **Foreign Application Priority Data**

Aug. 1, 2014 (JP) 2014-157462

(51) **Int. Cl.**

B41J 2/325 (2006.01)

B41M 5/50 (2006.01)

B41J 35/16 (2006.01)

B41M 5/382 (2006.01)

B41J 17/32 (2006.01)

B41M 5/28 (2006.01)

B41M 5/30 (2006.01)

B41M 5/34 (2006.01)

B41J 3/407 (2006.01)

B41J 2/32 (2006.01)

(52) **U.S. Cl.**

CPC **B41J 2/325** (2013.01); **B41J 17/32** (2013.01); **B41J 35/16** (2013.01); **B41M 5/28** (2013.01); **B41M 5/30** (2013.01); **B41M 5/34** (2013.01); **B41M 5/382** (2013.01); **B41M 5/502** (2013.01); **B41J 2/32** (2013.01); **B41J 3/4075** (2013.01); **B41M 5/345** (2013.01); **B41M 2205/04** (2013.01); **B41M 2205/30** (2013.01)

(58) **Field of Classification Search**

CPC **B41J 2/325**; **B41J 35/16**; **B41J 3/36**; **B41J 17/32**; **B41J 2/32**; **B41M 5/502**; **B41M 5/30**; **B41M 5/34**; **B41M 5/50**; **B41M 5/28**; **B41M 2/32**; **B41M 5/382**; **B41M 5/337**

See application file for complete search history.

(56) **References Cited**

FOREIGN PATENT DOCUMENTS

JP 56-126192 A 10/1981
JP 56-157395 A 12/1981

(Continued)

Primary Examiner — Julian Huffman

(74) *Attorney, Agent, or Firm* — ALG Intellectual Property, LLC

(57) **ABSTRACT**

Printing using two colors can be performed by a thermal print head. A base member, a thermosensitive color developing material layer formed by applying a thermosensitive color developing material on the entire surface of the base member, and a thermosensitive decolorizing material layer formed by applying a thermosensitive decolorizing material having a decolorizing temperature different from a color developing temperature of the thermosensitive color developing material on the entire surface of the thermosensitive color developing material layer, are provided.

7 Claims, 7 Drawing Sheets

